

WHAT IS CLAIMED:

1. A table comprising:

a main support section having a first main support

vertical member having a first and a second end, a second main

support vertical member having a first and a second end, a

5 first main support horizontal member having a first end

attached to said first end of said first main support vertical

member and a second end attached to said first end of said

second main support vertical member, and a second main support

horizontal member having a first end attached to said second

10 end of said first main support vertical member and a second end

attached to said second end of said second main support

vertical member;

a first side support section having a first side first

vertical member having a first and a second end, a first side

15 second vertical member having a first and a second end, a first

side first horizontal member having a first end attached to

said first end of said first side first vertical member and a

second end attached to said first end of said first side second

vertical member, and a first side second horizontal member

20 having a first end attached to said second end of said first

side first vertical member and a second end attached to said

second end of said first side second vertical member, said

first side first vertical member pivotably connected to said

first main support vertical member to enable pivoting of said

25 first side support section between a first position parallel
and closely adjacent said main support section and a second
position generally perpendicular to said main support section;

a second side support section having a second side first
vertical member having a first and a second end, a second side
30 second vertical member having a first and a second end, a
second side first horizontal member having a first end attached
to said first end of said second side first vertical member and
a second end attached to said first end of said second side
second vertical member, and a second side second horizontal
35 member having a first end attached to said second end of said
second side first vertical member and a second end attached to
said second end of said second side second vertical member,
said second side first vertical member pivotably connected to
said second main support vertical member to enable pivoting of
40 said second side support section between a first position
parallel and closely adjacent said main support section and a
second position generally perpendicular to said main support
section;

an upper support member pivotably attached to said second
45 main support horizontal member to enable pivoting of said
support section between a first position supported by said main
support and said first and said second side supports, and a
second position adjacent and generally parallel said first and
second side supports, supported by said main support.

2. The table as recited in claim 1 and further comprising an engagement structure carried by said upper support member for locking said upper support member to one of said first and said second side support sections in said first position, and for locking said upper support member to said main support in said second position.

3. The table as recited in claim 2 wherein said engagement structure further comprises:

a base portion attached to said main support horizontal member;

an extension portion attached to said based portion and having a lateral notch for facilitating engagement locking.

4. The table as recited in claim 1 wherein said an upper support member and said main support create a space within which at least half of said first and said second side supports fit when said upper support member is placed in said second position adjacent and generally parallel said first and second side supports, and said main support.

5. The adjustable table as recited in claim 1 wherein said first and second main support vertical members and said first and second side first vertical members all have open first ends and further comprising leg extensions fittable in

5 said open ends, said leg extensions are fixable within said first ends of said first and second main support vertical members and said first and second side first vertical members.